



HATFIELD-PROVIDING COST EFFECTIVE, CLEAR SOLUTIONS

HATFIELD REPLACEMENT FILTERS



YOUR **1ST** CHOICE FOR ALL YOUR FILTER NEEDS

Hatfield Wound Filter Cartridges are manufactured using high speed, continuous winding machines. This method provides a superior one-piece gradient density product. Our exclusive diamond shaped pattern produces flow tunnels that become progressively smaller from the outer diameter to the core. By progressively trapping contaminants as fluids travel to the center of the filter resulting in higher dirt holding capacities. This produces a greater quality product and better economies overall. Available in a wide selection of filter media, core, and end cap options insures material compatibility with most fluid applications.

HATFIELD OFFICE LOCATIONS

Houston	(281) 893-8870	Dallas/Ft. Worth	(972) 285-0115
Corpus Christi	(361) 853-5200	Freeport	(979) 265-9327
Midland/Odessa	(915) 337-4737	Austin	(512) 918-9663
Amarillo	(806) 358-7686	Oklahoma/Kansas	(918) 838-9987
Longview	(903) 757-3825	New Orleans	(504) 469-6432
Beaumont	(409) 866-6467		



www.hatfieldandcompany.com

VISA, MASTER CARD AND AMERICAN EXPRESS WELCOME

HATFIELD FILTER PART NUMBER

HATFIELD HF	MEDIA BC	MICRON RATING 5	DIAM. R	LENGTH 30	CORE S	CORE COVER -	CORE EX -
BC = Bleached Cotton		0.5	T = 2"	3.75" 30"	T - Tin Plated Steel	No Symbol None	E = Poly Core Insert
WC = White Cotton		1	E = 2-1/4"	4" 36"	P - Polypropylene	V - Specific Core Cover	E = 316SS Insert
NC = Natural Cotton		3	F = 2-3/8"	5" 39"	A - 316 Stainless Steel		EC = Extended Crimped Core
FP = FDA Polypro		5	R = 2-7/16"	6" 40"	S - 304 Stainless Steel		SOC = 222 O-Ring & Cap
NSF = NSF 41/61 Polypro		10	H = 2-5/8"	7" 50"	TW - Tin Steel Wild Cat		SOF = 222 O-Ring & Fin
EP = Ind. Polypro		15	S = 2-3/4"	8" 60"	PW - Polypro Wild Cat		06C = 226 O-Ring & Cap
PY = Polyester		20	L = 2-7/8"	9" 70"	SW - 304SS Wild Cat		06F = 226 O-Ring & Fin
NY = Nylon		25	P = 3"	9.75" 72"			PS = Poly spring
RY = Rayon		30	BB = 4"	10"			PM = Poly Cap & Metal Spring
FG = Fiberglass		40	J = 4-1/2"	12"			B = Buna Gasket
HG = Baked Fiberglass		50	K = 4-5/8"	12.50"			CSA = Standard 316SS Cap & Spring Assy.
FP = Fibrillated Polypro		75	X = Special	18"			W = Wildcat Cap & Spring
RT = Ryton		100		19.50"			ACS = 3" Tin Steel Cap & Spring
		125		19.75"			
		150		20"			
		200		27"			
				29.25"			
				29.50"			



HIGH PERFORMANCE, ABSOLUTE RATED DEPTH AND PLEATED FILTERS ALSO AVAILABLE!

CALL FOR ADDITIONAL INFORMATION